

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 03192132 A

(43) Date of publication of
application: 22. 08 . 91

(51) Int. Cl :
C08J 9/00
B29C 67/20
C08L 23/08
C08L 23/16
C08L 75/04
// B29K105:04
B29L 7:00

(21) Application number: 01331838

(71) Applicant: TONEN CHEM CORP

(22) Date of filing: 21 . 12 . 89

(72) Inventor: KAGAWA SEIJI

(54) PRODUCTION OF MICROPOROUS
ELASTOMER FILM

30-70wt.% ethylene/vinyl acetate copolymer and 70-30wt.% ethylene/propylene/ diene copolymer or polyurethane elastomer is kneaded and molded to obtain a film of a thickness of 10-40 μ m. This film is fed to the space between a heating roll heated to 100°C and an elastic roll at a feed rate of 2-30m/min in such a way that a (non)woven composition to the space between a heating fabric containing 40-200cc/m² of a mixture of water with optionally an alcohol is applied to the film on the side of the heating roll and an elastic roll in such a way that a specified (non)woven fabric is applied to the film on the side of the heating roll and heated to 100°C or higher under a pressure of 0.1-5kg/cm² to obtain the title film.

(57) Abstract:

PURPOSE: To produce a microporous film improved in waterproofness and gas transmissive property by feeding a film comprising a thermoplastic elastomer to the space between a heating roll heated to 100°C and an elastic roll at a feed rate of 2-30m/min in such a way that a (non)woven composition to the space between a heating fabric containing 40-200cc/m² of a mixture of water with optionally an alcohol is applied to the film on the side of the heating roll and an elastic roll in such a way that a specified (non)woven fabric is applied to the film on the side of the heating roll and heated to 100°C or higher under a pressure of 0.1-5kg/cm² to obtain the title film.

CONSTITUTION: A thermoplastic elastomer composition comprising, for example,

COPYRIGHT: (C)1991,JPO&Japio